

# elite mediQA

## double pass reverse osmosis units



500 - 4,000 l/hr

- High recovery rates; output flow rates from 500 to 4,000 l/hour.
- Units can be configured to run in multiple combinations to provide redundancy.
- Full colour touch screen display with comprehensive menu navigation including full schematics.
- Advanced data logging technology with password control.
- Data log file can be downloaded to a PC using a memory stick, providing access to historical performance data for full traceability.
- Semi-automated chemical cleaning program with on screen reminder function.
- Lightweight, corrosion resistant GRP or optional stainless steel pressure vessels.
- Compact, stainless steel skid mounted package.



# elite mediQA

## double pass reverse osmosis range

### description

Elite MediQA double pass RO units provide an innovative, high quality water purification system for haemodialysis and haemodiafiltration.

Our flexibility and strength of design ensures that the Elite MediQA range meets the needs of your dialysis requirements, now and in the future.

The range provides a unique set of benefits which allows unrivalled ease of operation and performance. All of our models meet the requirements of the Medical Device Directive 93/42/EEC and are CE marked as Class IIb Medical Devices.

### technical specification

	500 DP	750 DP	1000 DP	1500 DP	2000 DP	2500 DP	3000 DP	3500 DP	4000 DP	
<strong>Performance</strong>										
Permeate flow rate @ 10°C **	l/hr	500	750	1000	1500	2000	2500	3000	3500	4000
Drain flow	m³/hr	0.2	0.3	0.4	0.6	0.8	1.0	1.2	1.4	1.5
<strong>Dimensions</strong>										
Height	mm	1600	1600	1600	1600	1600	1600	1600	1600	1600
Width	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000
Depth	mm	1265	1265	1265	1265	1265	1265	1565	1565	1565
<strong>Weights</strong>										
Working	kg	453	462	508	525	593	636	689	771	879
Shipping*	kg	328	337	323	370	408	438	474	556	634
<strong>Services - Power</strong>										
Supply	V/ph/Hz	All units require 3-phase supply 400V +N+E 50/60 Hz								
Max current draw	Amps	14	15	16	19	21	22	22	22	22

Services - Connections		
Feed water	25 DN	Feed water connection 1" threaded female BSP
Concentrate	25 DN	
Permeate	25 DN	All connections in 1" sanitary tri-clamp
Ring return	25 DN	

Services - Feed water	
Pressure	Minimum feed water pressure 2 bar: maximum 6 bar
Free Chlorine	Following activated carbon, free chlorine level must be <0.1 ppm
Temperature	For optimum performance feedwater temperature should be between 5°C and 25°C
Total dissolved solids	Maximum feed water total dissolved solids 1000 ppm
Total hardness	All units require softened feed water with a total hardness of <4 ppm as CaCO <sub>3</sub>
S.D.I	Silt density index following final 5 micron filtration should be <5

### contact

**SUEZ Water Purification Systems Ltd**  
Bandet Way, Thame, Oxon OX9 3SJ

**Tel:** +44 (0)1844 217141 | **Fax:** +44 (0)1844 218098  
**Email:** [info@sueztreatmentsolutions.co.uk](mailto:info@sueztreatmentsolutions.co.uk)  
**Web:** [www.sueztreatmentsolutions.co.uk](http://www.sueztreatmentsolutions.co.uk)

\* Un-crated weight.

\*\* Variations in feed water temperature can affect output by up to ± 3% per degree Celsius.

